# Excel in Your Field

### **Specifications**

CATEGORY	XG3025	XG3025H	
ENGINE			
Гуре	Indirect, Swirl Chamber		
Model(Tier 4 Interim)	MHI S3L2		
Engine HP(Gross)	24.4		
PTO HP	19.2	17.1	
Rated speed, RPM	2,500		
Displacement-cu, in <sup>3</sup> .	80.4		
Fuel tank capacity(gal)	7.4		
Alternator(V-A)	12V - 50 Amps		
DRIVE TRAIN			
Transmission	Synchro Shuttle	HST	
No. of Speed	F12 x R12	3 Ranges	
Brakes	Wet, Multi - disc		
Steering	Hydrostatic Power Steering		
PTO			
Гуре	Independent		
Rear(rpm)	Standard (540 rpm)		
HYDRAULIC SYSTEM			
Control system	Position		
mplement pump, gpm	7.9		
Steering pump, gpm	4.6		
Total flow, gpm	12.5		
Category, 3pt hitch	CAT	CAT 1	
Hitch Lift capacity, lbs(Hitch end)	1,808		
Remote valves	Option		
DIMENSION			
Overall length, Frame to link, in.	118		
Overall width with tires, in.	54		
Wheelbase, in.	66		
Ht to top of rops, in.	88		
TIRE SIZE			
Ag Front / Rear	7 - 14 / 1	7 - 14 / 11.2 - 24	
ND Front / Rear	25 x 8.5 - 14 /	25 x 8.5 - 14 / 43 x 16 - 20	
Turf Front / Rear	25 x 8.5 - 14 /	41 x14 - 20	
WEIGHT			
Total weight without ballast, lbs.	2,434	2,469	

Front end Loader	LL3110
Tractor Application	XG3000 Series
Bucket, in.	66
Maximum Lift height, in.	94.3
Clearance with Attachment Dump, in.	64.3
Reach at Maximum Height, in.	18.2
Maximum Dump Angle, deg.	52
Maximum Rollback Angle, deg.	41
Digging Depth, in.	4.3
Overall Height in Carry Position, in.	51.3
Lift Capacity(@ Pivot pin), lbs.	1,600
Breakout Force(@ Pivot pin), lbs.	2,637
Approx. Weight (Loader w/o Bucket), lbs.	728

Backhoe	LB1106	
Tractor Application	XG3000 Series	
Digging Depth, in.	76.3	
Reach from centerline of swing Pivot, in.	113.1	
Loading Height, in.	63.6	
Swing Arc, deg.	180	
Transport Height, in.	77.2	
Bucket Rotating, deg.	180	
Stabilizer Spread(Down position), in.	68.7	
Stabilizer Spread(Up position), in.	46.4	
Bucket Digging force, lbs.	2,817	

### **Get More Standard Features**

- Power steering
- Switch operated Independent rear PTO
- ROPS with seat belt
- Hydraulic position control Differential lock
- Draw bar
- Pre-heat starting aid

- Safety flashers
- Fuel, coolant temperature, tachometer & hour meter aauaes
- Pre-heating, parking brake, battery charging, engine oil pressure, fuel filter, PTO operation and high beam operation/warning lights





LS Tractor USA | 6900 Corporation Parkway, Battleboro, NC P: 252.984.0700 | F: 252.984.0701 | www.lstractorusa.com **Dealer Imprint Zone** 

39000951-1605

# LS Tractor





- Eco-Friendly Tier4. 24.4HP, 3 cylinder fuel efficient engine
- 5 year warranty\*
- 12x12 synchro shuttle or 3 range HST with cruise control
- Front wheel mechanical assist 4WD
- Flat operator platform
- Choice of industrial, ag or turf tires at no additional cost
- Available sub-frame mounted, quick attach 6' backhoe

## **XG3000 Series** XG3025 / XG3025H Value Compacts

LSTRACTOR

# **Excel in Your Field**<sup>™</sup>

• Available quick attach front end loader with skid steer compatible bucket & grill guard

\*5-year limited warranty. See dealer for details

# XG3000 Series Value Compacts





Synchro Shuttle Transmission Models Makes changing direction easier than competitive non-shuttle gear models. 12 forward / 12 reverse gear transmission provides more operating speeds than others in its class for superior control, precision and safe operations for virtually any application



MHI Tier 4 Engine Good fuel efficiency with less noise and vibration



Your choice of tires Choose ag, industrial or turf tires at no additional cost





Optional quick attach front end loader with skid steer

Easy to take off or attach loader and easily change loader attachments. With up to 1,900 lbs of lift capacity it outperforms others in its class. Grill guard comes standard with loader rather than an option like others

compatible bucket

in its class

Rubber step mat Good quality rubber step mat can reduce vibration and noise and prevent slipping



PTO On/Off switch Best easy and safety Independent PTO control with electric on/off switch. User friendly design and location for simple PTO operation.



Easy open one-piece hood provides accessibility for easy maintenance



Simple gear range selections Select your gear range or 2WD/4WD with simple move of the levers



Optional quick attach backhoe Remove or attach in seconds. With 76" digging depth, 2,817 lbs of digging force and 180° swing arc, it outperforms other in its class

# Excel in Your Field



Comfortable seat Comfortable ride with deluxe cushioned seat even during long operations