

MT5 SERIES

LS Tractor



MT573C / MT573CPS
PREMIUM UTILITY TRACTORS

6-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

MT5 SERIES

PREMIUM UTILITY TRACTORS

RECOMMENDED IMPLEMENTS/ ATTACHMENTS



LOADER:

High Capacity With
An Abundance Of
Standard Features



LAND GRADER:

Heavy Steel Construction,
High Strength, Designed
For Use In Demanding
Applications



ROTARY CUTTER:

Durable Heavy Steel
Design Providing
Quality And Strength



BOX BLADE:

Features A Heavy
Welded Steel
Design For Use In
Demanding Applications

FEATURES

*6 Year Warranty**

73 Horsepower

F20 x R20 Synchro Shuttle And Power Shuttle Models

3 Rear Remotes

Spacious Cab 4 Post Cab

Over 6,600 lbs. Unit Weight Without Ballast

ROPS Configuration



Ergonomic Right-Side Console

*Provides Unobstructed
Access To Control Levers*



Integrated Loader Joystick

*Enables Precise Control Of
The Front-Loader*



Position And Draft Control Three Point

*Accommodates A Variety
Of Implement Needs*



Electric Engaged Independent PTO

*Readily Available To The
Operator To Control PTO
Implements*



Power Shuttle Transmission

*Enables Fast And Efficient
Directional Changes
(CPS Model Only)*




540/750/1000 PTO

*Provides Compatibility To A
Large Number Of Implements*



Hand Clutch

*The Hand Clutch Button
Added To The Gear Control
Lever Enables You To Change
Gears Easily*



Premium Seat

*The Air Suspension Seat
With 10 Degree Swivel For
Added Comfort*



Right-Side Door And Steps

*Provides Access To Both
Sides Of The Cab*

MT573C / MT573CPS



SPECIFICATIONS

CATEGORY		
ENGINE	MT573C	MT573CPS
Type	Vertical Water-cooled 4 Cylinder Diesel Engine	
Model	L4C25-T	
Emission	EPA Tier 4F	
Engine HP (kW)	73 (54.4)	
PTO (HP)	62	
Rated Speed (rpm)	2,500	
Displacement (in ³ .)	152.9	
Fuel Tank Capacity (gal.)	26.4	
DRIVE TRAIN		
Transmission Type (Option)	Synchro Shuttle	Power Shuttle
No. Of Speed	F20 x R20	
Forward Speed (mph)	0.11 - 19.4	
PTO		
Type	Independent	
Rear (rpm)	540 / 750 / 1,000	
HYDRAULIC SYSTEM		
Control System	Position / Draft	
Implement Pump (gpm)	13.2	
Steering Pump (gpm)	6.6	
Total Flow (gpm)	19.8	
Category (3pt Hitch)	CAT II	
Hitch Lift Capacity (lbs.) (Hitch End)	6,614	
Remote Ports	3 Pairs (Front), 3 Pairs (Rear)	
DIMENSION		
Overall Length (Frame To Link in.)	150	
Overall Width With Tires (in.)	77.5	
Wheelbase (in.)	84.6	
Height To Top (in.)	104.4	
Total Weight w/o Ballast (lbs.)	6,620	6,669
TIRE SIZE		
Front / Rear R14	W320/85R24 122D	W460/85R30 145D
Front / Rear Ag	11.2 - 24	16.9 - 30

FRONT END LOADER		LL6100
TRACTOR APPLICATION		MT5 SERIES
Bucket Size (in.)	78	
Maximum Lift Height (in.)	126.5	
Clearance With Attachment Dump (in.)	95.3	
Reach At Maximum Height (in.)	5.7	
Maximum Dump Angle (deg.)	64	
Maximum Rollback Angle (deg.)	38	
Digging Depth (in.)	7.0	
Overall Height In Carry Position (in.)	64.2	
Lift Capacity (At Pivot Pin) (lbs.)	3,626	
Breakout Force (At Pivot Pin) (lbs.)	6,644	
Approx. Weight (Loader w/o Bucket) (lbs.)	1,232	

Additional Equipment Available

- Power & Tilt Steering
- Switch Operated Independent PTO
- Front Loader Valve And 3rd Function Joystick
- Swivel Air Suspension Adjustable Seat (Cab Model)
- Deluxe Stereo System
- 7 Pin Electrical Connector
- Hydraulic Draft & Position Control With Auto Lift
- High Beam Operation / Warning Lights

**All Specs and features are subject to change, and pictures could include optional equipment etc.*



LS Tractor

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

